Cutting Heads

Rotary Heads

Bomford's Rotary Heads are ideal for longer growth material. Available with blades or heavy-duty chain cutting options,



operating in either vertical or horizontal plane, its 2.25msq cutting area makes short work of even the most challenging tasks

Ditch Cleaner

The new Bomford Ditch Cleaner is designed for use with a range of side-arm mowers, simplifying the maintenance of roadside ditches and grips. Two models are available in standard and high speed comprising a 660mm diameter rotary cutting head, powered by a multi-stroking radial piston motor.



Pro-Saw

The new ProSaw is suitable for use with all sizes of Bomford reach arm mower, from the Kestrel upwards. An alternative model is available, that includes a frame – the HRF (Hydraulic Reach Frame) - that enables the ProSaw to be mounted onto a telescopic handler or tractor loader. With

widths of 1.6m, 2.0m and 2.4m, the ProSaw comprises four circular saw blades capable of cutting through branches of up to 20cm (8").





Standard Duty Sheartrim

- hydraulic motor drive and Pitman wheel to 'sectional' reciprocating cutter bar
- standard 70mm sq clamp mount
- hydraulic flow divider and overloader protection
- maximum flow 60 litres per minute
- minimum flow 30 litres per minute
- maximum cutting ability 20mm diameter
- length available 1500mm

suitable for:

Robin, Kestrel, Hawk and Falcon



Medium Duty Sheartrim

- hydraulic ram and shuttle valve to solid tool steel cutter bar
- standard Bomford 70mm clamp mount
- overload / reversing valve protection
- maximum cutting ability 50mm diameter
- hydraulic requirement 34 45 litres per minute at 240 bar maximum
- lengths available 1600mm and 2000mm

suitable for:

Robin, Kestrel, Hawk and Falcon

Heavy Duty Sheartrim

- hydraulic ram and shuttle valve to solid steel cutter bar
- standard Bomford 70mm clamp mount
- overload reversing valve protection
- maximum cutting ability 100mm diameter
- hydraulic requirement 40 45 litres per minute at 240 bar maximum
- lengths available 1350mm and 2200mm

suitable for:

Falcon, Buzzard and B81-81

