

CUTTER BAR OPTIONS

90.012.01 RH
90.012.02 LH



1500 Cutter Bar

- Rear mounted piston motor with “wobble block” action to sectional knife
- Maximum cutting ability 20mm Diameter
- Cutting width 1500mm Specially designed for B315

WREN 90.012.03 LH 90.012.04 RH

Standard Sheartrim

**Kestrel
Harrier
Hawk
Falcon**

- Hydraulic motor drive and Pitman wheel to “sectional” reciprocating Bomford cutter bar
- Standard 70mm square clamp mount
- Hydraulic flow divider and overloader protection (max flow 60 litre/min - min flow 30 litre/min)
- Maximum cutting ability 20 mm diameter
- Length available 1500 mm only



90.015.02 RH
90.015.01 LH

Medium Duty Sheartrim

- Hydraulic ram and shuttle valve to solid tool steel cutter bar
- Standard Bomford 70mm clamp mount
- Overload/reversing valve protection
- Maximum cutting ability 50mm diameter
- Hydraulic requirement 34-45 litre/min at 240 bar max
- Lengths available 1600mm 2000mm

**Kestrel
Harrier
Hawk
Falcon**

90.015.07 2.00m

90.015.08 1.6m



Heavy Duty Sheartrim

- Hydraulic ram and shuttle valve to solid tool steel cutter bar
- Standard Bomford 70mm clamp mount
- Overload/reverse valve protection
- Maximum cutting ability 100mm diameter
- Hydraulic requirements 40-45 litre/min at 240 bar max
- Length available 1350mm 2200mm

**Falcon
Buzzard
B81 - 81**

90.015.05 1.35m

90.015.06 2.2m



For further information contact: www.bomford-turner.com

Tel: 0044 (0)1789 773383 Fax: 0044 (0) 1789773238 Email: sales@bomford-turner.com