

Bandit

The Bandit trailed flail mower is aimed at professional users where efficiency and finish are a must.

The Bomford Bandit mower range is built to withstand the toughest working conditions, remaining manoeuvrable when mowing tight up to walls and obstructions. The flexible design of the Bandit allows it to be front or rear mounted simply by turning the "A" frame around.

Key Features

- 1.5m or 1.8m or 2.25m cutting widths
- Fitted with roller as standard
- Variable cutting height
- Cat II three point linkage
- 540 or 1000 rpm PTO speeds
- Front or rear mount option



Want to know more about the Bandit range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: <http://www.bomford-turner.com/landscape/flail-mowers-and-toppers/bandit/>



Product Specification

Bandit	B1500	B1800	B2250
Cutting Width	1.5m / 4'11"	1.8m / 6'	2.25m / 7'2"
Transport Width	1.74m / 5'8"	2.05m / 6'9"	2.50m / 8'2"
Cutting Height	13-105mm / ½"-4'	13-105mm / ½"-4'	13-105mm / ½"-4'
No. of Flails	40	50	62
Flail Type	Pro / Bootee / BB	Pro / Bootee / BB	Pro / Bootee / BB
Full offset left of centre	700mm / 2'4"	700mm / 2'4"	700mm / 2'4"
Offset system	Manual	Optional Hydraulic	Hydraulic
Power management	30hp	50hp	90hp
Rear roller size (Diameter)	150mm / 6"	150mm / 6"	150mm / 6"
Weight (Approx)	470kg / 1036lbs	580kg / 1279lbs	650kg / 1433lbs