

Raptor

The new Raptor verge mower is the ideal choice for users who have a dedicated shoulder mowing operation to perform.

The Raptor can be front mounted allowing the fitting of a Bomford arm mower on the rear giving a 3.5m cut, in one pass. The Raptor can effortlessly work around street furniture and varying ground levels.

Key Features

- Cutting widths of 1.2, 1.6 or 2.0m.
- Front or Rear mounted options
- Banks cutting between 90° up and 50° down
- Cat II three point linkage
- Choice of flails



Product Specification

| Raptor | 1200 | 1600 | 2000 |
|---------------------|---------------------|---------------------|---------------------|
| Reach | 2.84m / 9'4" | 3.24m / 10'7" | 3.64m / 12" |
| Cutting Width | 1.2m / 4' | 1.6m / 5'3" | 2m / 6'6" |
| Max Offset | 750mm / 2'6" | 750mm / 2'6" | 750mm / 2'6" |
| No. of Flails | 32 | 44 | 54 |
| PTO Speed (rpm) | 1000 / 540 | 1000 / 540 | 1000 / 540 |
| Cowl Angle Movement | 140° (+90° to -50°) | 140° (+90° to -50°) | 140° (+90° to -50°) |
| Power Requirement | 40hp | 45hp | 70hp |
| Weight | 620kg / 1367lbs | 830kg / 1830lbs | 900kg / 1984lbs |
| Front Mountable | ○ | ○ | ○ |



Want to know more about the Raptor range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: <http://www.bomford-turner.com/landscape/flail-mowers-and-toppers/raptor/>