

# Turbo Mower

The Turbo Mower Elite, Euro, Open and Pro range offers operators a huge choice of cutting widths at very cost effective prices.

A well designed and constructed range, the Turbo Mower is built with durability and ease-of-use in mind – a low maintenance machine that is simple to operate.

## Key Features

- Choice of cutting widths available
- Front mount options
- 1.3 and 1.5 manual offset
- Hydraulic offset standard on 1.9m and above.
- Standard fitted roller and side skids
- Cat II three point linkage mounted
- Over run slip clutch protected



Want to know more about the Turbo Mower range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: <http://www.bomford-turner.com/landscape/flail-mowers-and-toppers/turbo-mower/>



## Product Specification

● Standard ○ Optional — Not Available

Turbo Mower	ELITE 130	ELITE 150	ELITE 190	ELITE 225	ELITE 245	ELITE 270
Working Width	1.3m/4'3"	1.45m/4'9"	1.9m/6'4"	2.26m/7'5"	2.42m/8'	2.72m/8'10"
Overall Width	1.47m/4'10"	1.63m/5'4"	2.1m/6'10"	2.45m/8'	2.6m/8'6"	2.9m/9'6"
Weight	213kg/469lbs	237kg/522lbs	451kg/994lbs	554kg/1221lbs	596kg/1313lbs	632kg/1393lbs
Hydraulic Offset	—	—	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated
Fully offset left of centre	—	—	400mm/15½"	400mm/15½"	400mm/15½"	400mm/15½"
PTO speed	540	540	540	540	540	1000
Front mount	—	—	—	—	—	—
No. of Flails (Whale Tail)	18	20	24	28	30	34
Power requirements	30-37hp	35-40hp	45-60hp	55-75hp	65-90hp	75-100hp
Cutting height	32-111mm 1¼"-4½"	32-111mm 1¼"-4½"	32-111mm 1¼"-4½"	32-111mm 1¼"-4½"	32-111mm 1¼"-4½"	32-111mm 1¼"-4½"
Roller size	114mm/4½"	114mm/4½"	140mm/5½"	140mm/5½"	140mm/5½"	140mm/5½"

Turbo Mower	EURO 250	EURO 280	OPEN 250	OPEN 280	PRO 250	PRO 270	PRO 300
Working Width	2.5m/8'3"	2.8m/9'2"	2.44m/8'	2.77m/9'1"	2.45m/8'	2.70m/8'10"	3.00m/9'10"
Overall Width	2.67m/8'9"	3m/9'10"	2.67m/8'9"	3m/9'10"	2.73m/8'11"	2.98m/9'9"	3.28m/10'9"
Weight	867kg/1911lbs	939kg/2070lbs	859kg/1893lbs	928kg/2045lbs	1210kg/2667lbs	1284kg/2830lbs	1390kg/3064lbs
Hydraulic Offset	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated
Fully offset left of centre	500mm/19½"	500mm/19½"	500mm/19½"	500mm/19½"	400mm/15½"	400mm/15½"	400mm/15½"
PTO speed	1000	1000	1000	1000	1000	1000	1000
Front mount	●	●	—	—	●	●	●
No. of Flails (Whale Tail)	28	32	28	32	20	24	26
Power requirements	65-110hp	75-110hp	65-100hp	75-110hp	68-80hp	80-120hp	95-135hp
Cutting height	43-88mm 1¾"-3½"	43-88mm 1¾"-3½"	32-111mm 1¼"-4½"	32-111mm 1¼"-4½"	45-157mm 1¾"-6¼"	45-157mm 1¾"-6¼"	45-157mm 1¾"-6¼"
Roller size	170mm/6¾"	170mm/6¾"	170mm/6¾"	170mm/6¾"	220/8¾"	220/8¾"	220/8¾"



### Adjustable guards

On some models the rear hood can be opened.



### Compact models

Machines for tractors over 800kg and above 30HP.



### Twin head stock

Front and rear mount options available.



### Auto adjust

Belt drive comes with auto-adjust system for better cutting results.