

Twin-Blade

The new, more robust Twin-Blade is a flexible, efficient, in-line topper or fully offset - perfect for paddocks and headlands.

The range extends from 1.8m and semi-offset (2.4m/2.7m) to 2.4m fully offset. The Twin-Blade also features cast-iron gearboxes and protected drivelines. Simple, adjustable skids on this machine are key to a smooth operation.

Key Features

- Shaft driven
- 1.8m, 2.4m, 2.4m offset and 2.7m cutting width
- Variable cutting height
- Shearbolt and overrun gear box protection
- Cat 1 or Cat II three point linkage
- A-Frame mounting option



Product Specification

Twin-Blade	TB180	TB240 Inline	TB270 Inline	TB240 Offset
Cutting Width	1800mm / 5'11"	2400mm / 7'10"	2800mm / 9'2"	2400mm / 7'10"
Overall Width (Transport)	1970mm / 7'6"	2571mm / 8'5"	2971mm / 9'9"	1850mm / 6'1"
Power Requirement (PTO)	22kW (30hp)	22kW (30hp)	22kW (30hp)	22kW (30hp)
Linkage Mounting	Cat I & II	Cat II	Cat II	Cat II
Offset Capability	Yes	Yes	No	Yes
Fully Offset Right of Centre	N/A	N/A	N/A	4350mm / 14'3"
PTO Speed	540rpm	540rpm	540rpm	540rpm
Number Of Rotors	1	2	2	2
Number Of Blade Carriers	1	2	2	2
Number Of Blades	2	4	4	4
Number Of Skids	2	2	2	2
Cutting Height	30-150mm 1¼"-6"	30-150mm 1¼"-6"	30-150mm 1¼"-6"	30-150mm 1¼"-6"
Weight	290kg / 640lbs	390kg / 681lbs	430kg / 948lbs	550kg / 1213lbs



Want to know more about the Twin-Blade range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: <http://www.bomford-turner.com/landscape/flail-mowers-and-toppers/twin-blade/>